

Product Code	AKPEROX BP 50 PASTE
Description	DiBenzoyl Peroxide, Paste, 50% in plasticizer. Produced in white and red colors. Different colors can be produced if requested.
Specifications;	
Density (@25°C)	: 1,10 - 1,14 gr/cm ³
Appearance	: In Red and White Colors, in paste form
Active Oxygen Content	: 3,1% –3,4%
Peroxide Content	: 49,0% –51,0%
SADT	: 50°C
CAS Nr	: 94-36-0
UN Nr	: UN 3108
Applications	AKPEROX BP 50 is used for curing unsaturated polyester (UP) resin based polyester putties, marble and stone adhesives.
Usage & Amount	Recommended to use 1% – 3% in general, according to climate conditions and product formulation. In order to obtain longer workable time, amount of usage should be reduced. It is usable with Amine and Cobalt accelerators.
Packaging	25 gr, 40 gr and 60 gr in tubes 30 kg PE Drum Different packages can be produced if requested
Handling & Storage	Must be kept between +5 C and +30 C. Keep pails tightly closed. Store and handle in a dry, well-ventilated place, away from sources of heat, ignition and direct sunlight in original packaging. Provide grounding and venting in order to prevent static electricity build-up. Avoid any contact with Amine and Cobalt Accelerators, acids, alkalis and heavy metal compounds such as driers and metal soaps.
Shelf Life	6 Months For unopened packages at recommended storage conditions

